

## Klea® Edge™ 444A

# Sustainable Refrigerant for the Automotive Aftermarket

**High-performing and economical  
alternative to R-1234yf**

Orbia Fluor & Energy Materials has over 70 years of experience delivering high-performing, sustainable refrigerant solutions to solve thermal management challenges. We leverage our technical and market expertise to deliver the best outcome for automotive aftermarket stakeholders.

Introducing Klea® Edge™ 444A, a new, direct replacement for R-1234yf for the automotive aftermarket. R-444A is a more economical and environmentally friendly option than R-1234yf\* and cools faster\*\* for enhanced passenger comfort.

R-444A provides the market options to meet current and future regulations for carbon emissions, while maintaining ease of use and recovery for service technicians and vehicle owners.

\*Based on market conditions as of September 2024.

\*\* Independant test lab data shows an improvement in cool down times.



# R-444A | Physical Properties

**Cool Down Rate:** Third party testing data showed R-444A has a cool down rate of 4 minutes faster than R-1234yf

Property	Units	R-1234yf	R-444A
ASHRAE 34 Classification	-	A2L	A2L
Global Warming Potential (GWP)*	-	4	93
Global Warming Potential (GWP) **	-	1	88
Relative COP***	-	100%	105%****
Relative Volumetric Capacity***	K	100%	112%
Typical Temperature Glide****	kg/m <sup>3</sup>	0	7
Liquid Density (20°C)	°C	1110	1140
Bubble Point	kPa	-29.5	-30
Saturated Vapor Pressure (20°C)	-	592	712

\*UK regulation (EU) No 517/2014 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 April 2014 on fluorinated greenhouse gases and repealing Regulation (EC) No 842/2006

\*\*EU Regulation (EU) 2024/573 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 7 February 2024 on fluorinated greenhouse gases, amending Directive (EU) 2019/1937 and repealing Regulation (EU) No 517/2014

\*\*\*Thermodynamic cycle calculation conditions: Single-stage, isentropic efficiency 65%, volumetric efficiency 100%, zero pressure drop Mean evap T = 10°C, Mean cond T = 40°C, Subcool = 5K, SH = 5K

\*\*\*\*105% for drop in for R-1234yf system, up to 112% if the system is optimized

## Pressure Temperature Chart

Black - Vapor		Bold - Liquid	
		R-444A	R-1234yf
°F	°C	(psig)	(barg)
-20	-28.9		0.4 0.0
0	-17.8	4.9 0.3	9.2 0.6
20	-6.7	16.0 1.1	21.6 1.5
40	4.4	31.6 2.2	38.4 2.6
60	15.6	<b>76.3</b> <b>5.3</b>	60.6 4.2
80	26.7	<b>109.1</b> <b>7.5</b>	89.0 6.1
100	37.8	<b>150.0</b> <b>10.3</b>	124.9 8.6
120	48.9	<b>199.9</b> <b>13.8</b>	169.2 11.7
140	60.0	<b>259.9</b> <b>17.9</b>	223.4 15.4
150	65.6	<b>294.1</b> <b>20.3</b>	254.7 17.6

## Benefits

- A2L Rating:** R-444A has been designated 'A2L' classification rating, by ASHRAE/ISO which means that it is mildly flammable and has low toxicity.<sup>1</sup>
- Regulatory Compliant:** R-444A with a GWP<sub>100</sub> <150 meets strict GWP targets (and complies with EPA Technology Transition Rules for many sectors). It has zero ozone depletion potential (ODP).
- Compatible\*:** R-444A will work with any system that uses R-1234yf.
- Easy to Use:** R-444A is a direct replacement replacement for R-1234yf in auto air conditioning. R-1234yf or R-134a service equipment can be re-purposed to service R-444A vehicles. Retrofitting can be completed with common A/C service tools.
- High Performing:** R-444A offers up to 10% higher cooling/heating capacity<sup>2</sup> in direct replacement scenarios compared to R-1234yf; 'Cold Air Faster'. It may also give higher energy efficiency, which will enable internal combustion engine vehicles to see improved fuel economy. Electric vehicles may experience extended range. Both leading to an improved passenger experience.

- Affordable:** R-444A is an economical alternative to R-1234yf.<sup>3</sup> Charge size is the same as R-1234yf.
- Sustainable:** R-444A has a comparable carbon footprint<sup>4</sup> compared to R-1234yf with minimal TFA derogation in the atmosphere.<sup>5</sup>
- Stable:** R-444A is chemically stable, its composition remains in specification from charging through recovery from a/c systems, with no known polymerisation.<sup>6</sup>
- Service Equipment:** Service tools and equipment are being made available by leading manufacturers. The dedication and use of existing equipment is also an option.

<sup>1</sup> See applicable regional regulations codes and product/standards which cover the use of flammable refrigerants, e.g. ASHRAE standard 15.

<sup>2</sup> Third party test data from automotive application confirmed R-444A delivered 2-3°C colder air and 4-minute faster pulldown to 22°C than R-1234yf.

<sup>3</sup> Based on market conditions as of July 2025.

<sup>4</sup> LCCP CO<sub>2</sub> Equivalent Emissions during Vehicle's Lifetime.

<sup>5</sup> Based on the findings EFCTC Position Paper 08 October 2021 which states 'HFO-1234ze, HFO-1336mzz and HCFO-1233zd are broadly estimated to contribute less than 0.01 µg/L to the average concentration of TFA in European rainwater through to 2050'.

<sup>6</sup> Based on internal laboratory testing.



Information contained in this publication, or as otherwise supplied to the Users is believed to be accurate and given in good faith, but none of the information that is disclosed in this publication constitutes any representation, warranty, assurance, guarantee or inducement by Mexichem Fluor Inc. and its subsidiaries (doing business as Orbia Fluor & Energy Materials) to the User with respect to the content or accuracy of the information contained within this publication. It is for the User to satisfy itself of the suitability for its own particular purpose and Mexichem gives no warranty as to the fitness of the Product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that such exclusion is prevented by law. Nothing in this publication shall be construed as a warranty, assurance, or guarantee by Mexichem to the Users with respect to infringement of patents or copyrights or other rights of third parties; freedom under Patent, Copyright and Design cannot be assumed. Mexichem accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Klea® Edge™ is a registered trademark of Mexichem Amanco Holding, S.A. de C.V.

For more information, contact  
[fem@orbia.com](mailto:fem@orbia.com)

[orbia-fem.com](http://orbia-fem.com)

FMC\_FLY\_R\_444A\_25\_ENUK\_R01

Klea® Edge

orbia

Fluor & Energy  
Materials